



SPECIFICATION

- 1. Rated Voltage : AC240V±10%
- 2. Rated Current : 10A
- 3. Maximum Current Consumption : 20mA
- 4. Withstand Voltage : 1.5kV
- 5. Insulation Resistance : 10MΩ
- 6. Turn-On Level : 10~16lx
- 7. Turn-Off Level : 35.5~56lx
- 8. Operating Temperature Range : -10℃~40℃
- 9. Humidity Resistance : 95% RH

* Reference to the KAGA, INC. Specification R4A002768

COMPONENT PARTS LIST

ITEM No	DESCRIPTION	QUANT	MATERIAL
9	Marking	1	Fine Quality Paper
8	Screw	2	Mild Steel
7	Blade of Load Side	1	Brass
6	Blade of Common Side	1	Brass
5	Blade of Power Source	1	Brass
4	Gasket	1	Chloroprene Foam Rubber
3	Lighting Window	1	PMMA Resin
2	Base	1	PBT Resin
1	Cover	1	PP Resin (Color: Maroon)

unit: mm

MARK	CORRECTED	CAREER	DATE	SIGN	DESINE	ARTICLE	PHOTOELECTRIC CONTROLS
					H.Mitsuda	MODEL	SS-2410C
					17.May.'05 H.Mitsuda	DRAWING No.	R3A002278A
					17.May.'05 T.Sakamuro	SCALE	S=1/1
					17.May.'05 H.Shinzaki	DATE	17.May.'05

KAGA, INC.