

AUSTEKNIS

Bright and exciting



N O M O ' S

HP1000

- 01 Outer mechanism: Aluminium
- 02 Slim/ Compact/ Light weight/ Simple yet beautiful designed
- 03 Extended fixture's size that enables the solar cells to absorb naturally more power from the sun.
- 04 Triple ways of installation
 - A) On pole
 - B) Wall mounted
 - C) On extended/ outstretched arm

- 05 Quick charging, for illuminating overnight.
- 06 Built-in motion sensor, optional working operating modes.
- 07 Low cost
- 08 Easy installation



SPECIFICATION

Specifications	HP 1000
Light output	2500LM
Battery-type	Newest generation LIFEP04 battery
Battery Capacity	80WH
Solar panel	25W
Solar cells	Very high efficiency-proprietary solar cells (greater than 21.5%)
Solar panel-Service life	25 years
Recommended pole height	<6m
Pole installation	On pole; Wall mounted; On extended/outstretched arm
Working time	≥30 hours
Dimensions (L x W x H)	550*183*80
Operating temperature	-15°C to +70°C
Protection rating	IP65 Certificate

Austeknis Pty Ltd 7 Seaview Road, Lynton, South Australia 5062

Phone: +61(8) 8276 3533

Fax: +61(8) 8277 3405

Email: sales@austeknis.com www.austeknis.com



Quality and Knowledge That Lights Your Way